

C-CONTAINER FRIENDLY

Available configurations:



BATTERY TENSION

RH series

80V 96V

SBE Side battery extraction

AC series

80V 96V

120V

Rear battery extraction

RH60-C-SBE



AC120-6-C



AC80-9-C0-C



VERSIONS

LT Low tilt cylinders CO Compact - 12 on given dimensions

R Remote control



TYRES

Front single or twin
SE: solid tyres
CU: cushion in rubber
PL: cushion in polyurethane



CABIN

- Cover head guard
- Upper covering and front window with wiper
- Rear window with wiper
- Upper covering, front and rear windows with wipers, PVC doors
- TGV - full metal frame cabin complete of doors, windows and wipers



TOOLS AND DEVICES

- Working LED lights with DC/DC controller
- Road lights - low/high beam, flashing indicators, stop
- Blue spot light
- Heater and/or Air conditioning
- Front and rear defroster
- Infrared led video camera with colour LCD 5" display
- Radio with CD/Mp3 player, battery socket 12/24V
- Speed reduction while lifted forks
- Safety pedestrians and obstacles



COMMAND CONTROLLERS

- Levers
- Electro hydraulic distributor with mini-fingers, forward/reverse switch and horn buttons in the armrest

5,000 kg to 12,000 kg @ 600 mm
11,000 lbs to 26,500 lbs @ 24"

The C- Container configuration is dedicated to the usage of the forklift inside a container. The range of forklifts that can be ordered with this configuration goes from 5 to 12 ton, at 600 mm load center.

The peculiarity of this series is that the maximum height dimension does not exceed 2200 mm.

SECTORS:

- paper
 - cotton
 - steel and aluminium
 - beverage
 - automotive
 - timber
 - general manufacturing
 - heavy logistics
 - concrete and brick
 - recycling
- RH50 - 60 - 70 offer **high performances** and zero emissions.
 - Line choice for **reliability** demonstrated when subjected to heavy loads and continuous work on multiple shifts.
 - Flexibility in the use in **indoor and outdoor** areas, with different types of flooring.
 - AC series 8000 kg - 8000 kg at 900 mm - 10000 kg - 12000 kg:**
 - AC Forklifts series AC80-6 - 80-9 - 100L-6 - AC120-6** were developed to move **large and heavy loads in tight spaces** and in **different climatic conditions**.
 - Using AC technology -ALTERNATING CURRENT-** to manage the traction motor 32kW (80V) / 38kW (96V) / 47kW (120V) and the lifting pump motor 45kW (80V) / 52kW (96V) / 54kW (120V), **improving performances, autonomy and longevity of charged battery**.
 - External mast chains and high view cabin** allow the operator to manoeuvre the forklift in surrounding areas promoting a safe workplace.
 - Rear infrared LED video camera** with flat colour monitor to make safe and visible handling operations.
 - Safe and ergonomic entry into the cabin with an optimal driver's seat position.
 - Grammer seat** provides high comfort to the driver.
 - Reliability** guaranteed by particularly robust frames and masts, which are able to withstand external stresses.
 - Working in **long and frequent operation** shifts.
 - Applications with **special equipment** - paper clamps, coil booms, multiple forks.
 - Indoor / outdoor** operations in different ground conditions.
 - Quick battery replacement** with another forklift or a crane.

